

G·7 Spot

IP 66 LED moving head

The G·7 Spot is the quintessence of IP-rated moving heads.

A fast, compact, and lightweight mid-sized moving head spot with high-output and low power consumption.

Thanks to its white LED engine and CMY color mixing, the G·7 Spot is the perfect moving head for those who need maximum light output inside an easy-to-move luminaire.

The G·7 Spot gives you a solid construction, a high-quality beam, and an optimal projection in a very flexible assembly.

Designed to work as hard as you do.



 **SGM**[®]



Product Specifications



TruColor™
Full Range LED Calibration
Monitored Consistency
Color Match



ThermalDrive™
Advanced Temperature Control
Predictive Algorithm
Hybrid Cooling



DryTech™
Integrated Patented Dehumidification
Active Moisture Removal
IP66 Rating



PHOTOMETRIC DATA

- 350w with 6,500k White LED Engine
- 16,000 Lumens
- 35.8 Lm per Watt
- 5° - 39° Zoom Range
- L70 @ 20,000hrs
- Linear CTO (3,200k-6,500k), CTB

ELECTRICAL

- 100-277v AC 50 / 60hz
- Max. Power 445W / Typical 415W
- Power Thru 14 Amps
- Overload Protection with Automatic Recover
- Inbuilt IP67 Auto-Switch Power Supply

PHYSICAL

- 17.1 x 24.5 x 14.6 inches (433 x 622 x 370 mm)
- 59.5 lbs (27 kg)
- IP 66
- Color: Black, White, Custom RAL
- AR Coated Glass
- Material: Aluminium, Steel, PC / ASA, Rubber

CONNECTIONS AND CONTROL

- IP 67 5 pin XLR In / Out
- IP 66 True1 Compatible Power In / Out
- Lumen Radio Wireless DMX
- 22 or 29 DMX Modes
- Protocol Support: CRMX, W-DMX™ G2 / G3 / G4 / G4S, DMX512A, RDM ANSI E1.20

FEATURES

- Gobo Wheel 1: 5 + Open, Rotating
- Gobo Wheel 2: 9 + Open, Static
- Motorized Focus
- Motorized Zoom
- 3 Facet Prism, Rotating
- Iris 1%-100%, Pulsing
- CMY Color Mixing, RGB Macros
- Color Wheel: 5 + Open
- High CRI Enhancer
- Digital and Mechanical Animation
- Pan: 250° / Tilt: 640°
- High Speed Strobe (1-50 Hz)
- 16-bit control dimmer, colors, CTO, pan/tilt, gobo index/rotation, zoom, focus
- Frost

ORDERING INFORMATION

- 80102505 G · 7 Spot, Std, BL
- 83061184 G · 7 Spot Top Hat
- 83060602 Omega Bracket with 1/4-turn fasteners
- 07860040 IP Power Cable
- 83062011 SGM USB uploader cable
- 83061136 Vacuum Test Kit
- 80070217 A · 4

POI OPTION AVAILABLE

Designed for Permanent Outdoor Installations, the POI product package is specifically developed for durability and endurance in harsh environments.

All POI Fixtures include IP66 rating, C-5M marine protection, 5 year warranty and **DryTech™** technology.

CERTIFICATIONS & CLASSIFICATIONS



RoHS IP66